

GUIDE SPECIFICATIONS FOR SURFACING HOT MIXED ASPHALT TENNIS COURTS

PART 1 – SCOPE OF WORK

1.01

Work Included

This work includes furnishing and installing surfacing and striping for asphalt tennis courts.

1.02

Description of System and General Conditions

This Specification shall define the Color Coating system application and striping applications for asphalt tennis courts. All work required for Sub-base construction, drainage, fencing, and asphalt is outlined in the specification of the American Sports Builders Association (USTC & TBA).

1.03

Contractors Pre-Qualification Requirements

- a) Contractor must have experience with similar projects, and must provide owner with list of jobs completed within the last 5 years.
- b) Contractor must supply owner with sample of proposed product for prior approval
- c) Contractor must be a member in good standing with the American Sports Builders Association (United States Tennis Court and Track Builders Association). This is to ensure that the contractor has met the requirements set forth to be able to perform this specialty work.
- d) Contractor should be licensed in the state of which the work is to be performed and entitled to practice the following classifications: Tennis Court and Running Track facilities.
- e) Contractor must use materials that meet the guidelines and specifications for the American Sports Builders Association (United States Tennis Court and Track Builders Association).

1.04

Contractors Responsibility

- a) Furnish owner with an estimated start date.
- b) Start and complete project in a timely manner as specified in the contract documents.
- c) Furnishing all labor, materials, equipment and taxes to fully execute job.
- d) Furnish and maintain temporary flagging and barricades as required to protect employees and public at all times.
- e) Daily clean-up of trash and debris.
- f) Contractor must carry proper insurance. (A 30 day cancellation notification shall apply to all policies).

1.05

Insurance Requirements

- a) ***Commercial General Liability***
 - General Aggregate \$2,000,000
 - Personal Injury \$1,000,000 per occurrence
 - Each occurrence \$1,000,000
- b) ***Commercial Business Automobile Liability***
 - Combined Single Limit of \$1,000,000 per occurrence
- c) ***Workers' Compensation***
 - Bodily Injury by Accident \$1,000,000 per accident
 - Bodily Injury by Disease \$1,000,000 per accident

1.05.1**Quality Assurance**

- a) Upon request from owner, contractor shall supply owner with a list of similar projects and its contacts that have been successfully completed within the last three years. (pictures may be required)
- b) Contractor shall provide owner with a reference letter of good standing from the material manufacturer.

1.06**Warranty**

All surfacing materials and labor shall be warranted for a period of no less than one (1) year.

1.07**Approved Manufacturer/Installer/**

Quality Court Industries
5661 Brownsfield Dr.
Baton Rouge, LA 70811
225-774-9974 – phone
225-774-9984 – Fax
www.qualitycourts.com

PART 2- MATERIALS FOR COLOR COATING SYSTEM**2.01****Approved Materials**

- a) World Class – Patch Binder – (Latex cement additive)
- b) World Class – Acrylic Resurfacer
- c) World Class – Color Concentrate – (paint)
- d) World Class – Textured Line Paint
- e) Sand – 80 - 120 Mesh
- f) Water – Clean and Fresh

PART 3- SURFACING PROCEDURES**3.01****Surface Preparation**

The surface to be coated must be sound, have adequate drainage, and must be pressure washed to remove any dirt, grease, dust, and or any delaminated areas. All patching must be completed before surfacing materials are applied.

3.02**Flooding and Patching**

Slab must be flooded to expose birdbaths (areas that hold water). Flood slab, then allow slab to drain for 1 hour. Mark all birdbaths that are greater than 1/8" (nickel depth). All birdbaths must be patched using the Word Class Patch Binder Mix. All areas that need patching shall be primed first. Adequate parts of patch binder, silica sand, and Portland shall be blended together and applied for a resilient patch. All patches shall blend in to existing slab. Some sanding may be required for blending.

3.03

Base Coat

Apply two coats of World Class Acrylic Resurfacer to improve the look and planarity of the slab, provide a tight blemish free base, and to provide better adhesion for the paint surface. Adequate parts of sand, water, and Acrylic Resurfacer shall be blended together to provide a resilient base. Acrylic Resurfacer shall be applied by method of squeegee for the purpose of filling in small pits and covering small voids. (Slab shall be scraped between all coats to remove trash that may collect while applying)

3.04

Paint Surfacing

Apply two coats of World Class Color Concentrate (Tennis Court Paint). Adequate parts of sand, water, and Color Concentrate shall be blended together to provide a resilient Surface. Paint shall be applied by method of squeegee for the purpose of filling in small pits and covering small voids. Allow enough time for paint coats to thoroughly dry before reapplying. (Slab may need to be scraped before applying second coat of paint)

3.05

Line Striping

Apply two coats of textured line paint after final surfacing coat is thoroughly dried. Lines must be 2" in width and shall conform to the regulations set forth by American Sports Builders Association (USTC & TBA).

PART 4-COLOR

4.01

Color of Courts.

Standard Colors are as follows: Dark Green, Medium Green, Light Green, Brick Red, Khaki, Delta Blue, Coral, Maroon, and Chocolate. Specialty colors can be made upon request. Color will be chosen by owner or owner's representative, and must be made a minimum of 72 hours before bid date.

4.02

Color Layouts and Scheme

Tennis court color scheme shall be either solid color (one tone) or a two color (two tone) color scheme. Color schemes shall be chosen by owner or owner's representative, and must be made a minimum of 72 hours before bid date.

PART 5 – LIMITATIONS

Material Limitations

Surfacing materials shall not be applied when temperatures are below 50°F or if temperatures are above 130°F. Do not apply material if slab is wet or if rain is apparent. Do not store materials in direct sunlight. Do not allow material to freeze. Keep containers sealed until use.

**FOR SPECIFIC PROJECT SPECIFICATIONS, OR OTHER SPORTS APPLICATIONS,
OTHER COLORS OR FOR FURTHER INFORMATION, PLEASE CONTACT:
QUALITY COURT INDUSTRIES (225) 774-9974 or visit our website at
www.qualitycourts.com**